FEATURES｜產品特點


Perfect track of seam line on the waist band

縫線密合，完美呈現



Tension controlled by puller and stepper motor for suitable sewing circumference.

採用步進馬達滑台控制車縫周長，可依車縫尺寸進行設定



Siruba Roller System rotates bi-direction to ensure a smooth garment feeding.

特殊穩布結構，可雙向轉動確保送布順暢，車縫穩定




Instinct operation with touch panel. Easy to learn and operate.

觸控式操作面板
易學易操作



SPECIFICATION｜產品規格

型號 Model	**ASC-UWB100**
搭配縫紉機機頭 Machine Head	SIRUBA C007K-W532 /CR
車縫速度 Sewing Speed	3500 SPM (最高 Max)
使用針型 Needle Type	UY×128GAS #11
鬆緊帶寬度 Elastic Width	20~55mm
車縫圓周範圍 Perimeter Range	 前後裁片高低差 3cm Front & back panel height differences ≤ 3cm
氣體消耗量 Air Consumption	400 L/min
氣壓 Air Pressure	0.5 Mpa
電源電壓 Power Supply	Single Phase 1Φ AC200~240V 50/60Hz
消費電力 Power Consumption	1000 W (Max)
機器尺寸 Machine Dimensions	(W)1100×(D)1000×(H)1750mm (With table and thread stand 含桌板、線架)
生產效率 Production Capacity	67cm・產能：9.5 sec/件、車縫速度：3500 SPM 67cm・Cycle time: 9.5 sec/piece、Sewing speed: 3500 SPM

TOP 100 TAIWAN BRANDS

ISO 9001:2000
ISO 14001:2004

高林股份有限公司
KAULIN MFG. CO., LTD.

由於對產品的改良及更新，本產品型錄之產品規格及外觀的修改恕不事先通知！

The specification and appearances of the equipment described in this catalogue are subject to change without previous notice.

FEB.2019

ASC-UWB100

銀箭牌

Automatic Waistband Attaching Sewing Machine

褲頭自動上腰機



SiRUBA
AUTOMATIC SYSTEM